

## HYDRAULIC BOLT TENSIONING

### Air Driven Power Packs



#### Power Pack Features

- Output pressure up to 2500 bar
- Air driven hydraulic pump
- Easy to use
- Mounted in robust tubular steel transportable frame 40 x 40 x 44 cms
- Colour coded to match hoses and tools
- Complete with, air inlet filter, pressure regulator and lubricator
- Dual scale, damped, calibrated oil pressure gauge
- 8 litre capacity reservoir fitted with extra direct return
- Medium ISO 10 oil

#### Options

- Stainless steel frame
- Chart recorder
- Water medium
- Stainless steel tank
- Stroke counter
- Remote control
- Pressure transducer
- Digital output to PC
- Custom design

Part Number	Working Pressure (bar)	Minimum Air Inlet Pressure (bar)	Oil Delivery cc/stroke	Air Consumption litre/min	Pack Weight kgs
BT-1006	1000	4	1.6	800	19.5
BT-1007	1000	6	6	1600	23
BT-1506	1500	4	1	800	19.5
BT-1507	1500	6	4.5	1600	23
BT-2006	2000	5	1	800	19.5
BT-2007	2000	6	3	1600	23
BT-2506	2500	5	3	1600	23
BT-2507	2500	7	2	1600	23



**BOLTIGHT®**  
HYDRAULIC BOLT TENSIONING

BOLTIGHT is the UK  
Registered Trade Mark  
of Boltight Limited