

HYDRAULIC BOLT TENSIONING

1500 bar Flexible Hose Assemblies

These 1500 bar working pressure hose assemblies are manufactured from multi spiral reinforced high pressure flexible hose, colour coded BLUE. They are delivered fully assembled with self sealing quick connect couplings and nipples for fast and clean operation. The quick connectors are fitted with BLUE plastic dust caps.

Hoses are assembled, filled with oil and pressure tested prior to despatch. Test certificates are available. All hoses are marked with serial numbers for identification. Hoses are assembled with a clear PVC cover for additional protection

against abrasion and chemical attack.

Minimum burst pressure is 4500 bar and the minimum bend radius is 150 mm. Minimum hose length is 1m. Hoses are available in multiples of 0.1m length. These hose assemblies conform to the requirements of the European Pressure Equipment Directive and are CE marked.

Special hose assemblies can be made to meet your needs. Please send details of your requirements for a fast response.




BT-1540-N Hose




BT-1541-N Hose




BT-1542-N Hose




BT-1548-N Interconnecting Hose



BT-1550-N Interconnecting Hose



BT-1549-N Interconnecting Hose



BT-1558-N Interconnecting Hose

N = Hose length in metres



001

BOLTIGHT[®]
HYDRAULIC BOLT TENSIONING

BOLTIGHT is the UK
Registered Trade Mark
of Boltight Limited

FMA 001 B

Boltight Limited, Unit 2, Junction 10 Business Park, Bentley Mill Way, Walsall, West Midlands, WS2 0LE, United Kingdom.

Tel: +44 (0)845 500 5556 Fax no. +44 (0)845 500 5557

email: sales@boltight.com www.boltight.com